
















# RX Micro Grain Carbide

RX超微粒碳化鎢系列

Micro Grain Carbide

# RX MG



	超微粒碳化鎢端銑刀	標準型二刃	..... P19~P20
	超微粒碳化鎢端銑刀	標準型四刃	..... P20
	超微粒碳化鎢端銑刀	長刃型二刃	..... P21
	超微粒碳化鎢端銑刀	長刃型四刃	..... P21
	超微粒碳化鎢端銑刀	長柄型二刃	..... P22
	超微粒碳化鎢端銑刀	長柄型四刃	..... P22
	超微粒碳化鎢球銑刀	標準型二刃	..... P23
	超微粒碳化鎢球銑刀	標準型四刃	..... P23
	超微粒碳化鎢球銑刀	長柄型二刃	..... P24
	超微粒碳化鎢球銑刀	長柄型四刃	..... P24
	超微粒碳化鎢高螺旋端銑刀	標準型二刃	..... P25
	超微粒碳化鎢高螺旋端銑刀	標準型三刃	..... P25
	超微粒碳化鎢高螺旋端銑刀	長刃型二刃	..... P26
	超微粒碳化鎢高螺旋端銑刀	長刃型三刃	..... P27
	超微粒碳化鎢圓角銑刀	標準型二刃	..... P28
	超微粒碳化鎢圓角銑刀	標準型四刃	..... P29
	超微粒碳化鎢圓角銑刀	長柄型二刃	..... P30
	超微粒碳化鎢圓角銑刀	長柄型四刃	..... P31
	超微粒鎢鋼鑽頭	短刀型	..... P32



# RX Micro Grain Carbide

RX超微粒碳化鎢系列

Micro Grain Carbide

# RX MG



特點:

1. 加工不銹鋼材質，效果最佳。
2. 粗加工、精加工兼具之切削刀具。
3. 使用水溶性切削液，效果最佳化。

Features

1. Best performance in processing stainless steel.
2. Applicable to both rough machining and finishing.
3. Optimized performance by the use of water-soluble cutting fluid.

## EMEA

MG

TiAlN

35°

HRC 52

Oil

Oil

Oil

Oil

端銑刀-標準型二刃

Standard End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L. O. C	全長 O. A. L
EMEA204010	1.0	4.0	2.5	50
EMEA204015	1.5	4.0	4	50
EMEA204020	2.0	4.0	5	50
EMEA204025	2.5	4.0	6	50
EMEA204030	3.0	3.0	8	50
EMEA203030	3.0	4.0	8	50
EMEA204035	3.5	4.0	9	50
EMEA204040	4.0	4.0	10	50
EMEA206010	1.0	6.0	2.5	50
EMEA206015	1.5	6.0	4	50
EMEA206020	2.0	6.0	5	50
EMEA206025	2.5	6.0	6	50
EMEA206030	3.0	6.0	8	50
EMEA206035	3.5	6.0	9	50
EMEA206040	4.0	6.0	10	50
EMEA206045	4.5	6.0	11	50
EMEA206050	5.0	6.0	13	50
EMEA206055	5.5	6.0	14	50
EMEA206060	6.0	6.0	15	50



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 粗加工、精加工兼具之切削刀具。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel
2. Applicable to both rough machining and finishing.
3. Optimized performance by the use of water-soluble cutting fluid.

EMEA

MG

TiAlN

35°

HRC  
52°

端銑刀-標準型二刃

Standard End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L. O. C	全長 O. A. L
EMEA208065	6.5	8.0	18	60
EMEA208070	7.0	8.0	18	60
EMEA208075	7.5	8.0	20	60
EMEA208080	8.0	8.0	20	60
EMEA210085	8.5	10.0	20	75
EMEA210090	9.0	10.0	22	75
EMEA210095	9.5	10.0	22	75
EMEA210100	10.0	10.0	25	75
EMEA212105	10.5	12.0	25	75
EMEA212110	11.0	12.0	25	75
EMEA212120	12.0	12.0	30	75
EMEA216130	13.0	16.0	35	100
EMEA216140	14.0	16.0	35	100
EMEA216150	15.0	16.0	40	100
EMEA216160	16.0	16.0	40	100
EMEA220180	18.0	20.0	40	100
EMEA220200	20.0	20.0	40	100
EMEA225220	22.0	25.0	40	100
EMEA225250	25.0	25.0	40	100



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 粗加工、精加工兼具之切削刀具。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. Applicable to both rough machining and finishing.
3. Optimized performance by the use of water-soluble cutting fluid.

EMEA

MG

TiAlN

3.5°

HRC 52°

5

OIL

H

M

端銑刀-標準型四刃

Standard End Mills - 4 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L. O. C	全長 O. A. L
EMEA404010	1.0	4.0	2.5	50
EMEA404015	1.5	4.0	4	50
EMEA404020	2.0	4.0	5	50
EMEA404025	2.5	4.0	6	50
EMEA404030	3.0	3.0	8	50
EMEA403030	3.0	4.0	8	50
EMEA404035	3.5	4.0	9	50
EMEA404040	4.0	4.0	10	50
EMEA406010	1.0	6.0	2.5	50
EMEA406015	1.5	6.0	4	50
EMEA406020	2.0	6.0	5	50
EMEA406025	2.5	6.0	6	50
EMEA406030	3.0	6.0	8	50
EMEA406035	3.5	6.0	9	50
EMEA406040	4.0	6.0	10	50
EMEA406045	4.5	6.0	11	50
EMEA406050	5.0	6.0	13	50
EMEA406055	5.5	6.0	14	50
EMEA406060	6.0	6.0	15	50
EMEA408065	6.5	8.0	18	60
EMEA408070	7.0	8.0	18	60
EMEA408075	7.5	8.0	20	60
EMEA408080	8.0	8.0	20	60
EMEA410085	8.5	10.0	20	75
EMEA410090	9.0	10.0	22	75
EMEA410095	9.5	10.0	22	75
EMEA410100	10.0	10.0	25	75
EMEA412105	10.5	12.0	25	75
EMEA412110	11.0	12.0	25	75
EMEA412120	12.0	12.0	30	75
EMEA416130	13.0	16.0	35	100
EMEA416140	14.0	16.0	35	100
EMEA416150	15.0	16.0	40	100
EMEA416160	16.0	16.0	40	100
EMEA420180	18.0	20.0	40	100
EMEA420200	20.0	20.0	40	100
EMEA425220	22.0	25.0	40	100
EMEA425250	25.0	25.0	40	100



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 刃長為刃徑之5倍，適合側面大面積加工。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. The blade length is five times as the diameter, suitable for the processing of large lateral surface.
3. Optimized performance by the use of water-soluble cutting fluid.

EMEB

MG

TiAlN

35°

HRC 52°



端銑刀-長刃型二刃

Long Flute End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
EMEB206030	3.0	6.0	15	75
EMEB206040	4.0	6.0	20	75
EMEB206050	5.0	6.0	25	75
EMEB206060	6.0	6.0	30	75
EMEB208080	8.0	8.0	35	100
EMEB210100	10.0	10.0	45	100
EMEB212120	12.0	12.0	50	100
EMEB216140	14.0	16.0	70	150
EMEB216160	16.0	16.0	70	150
EMEB220180	18.0	20.0	75	150
EMEB220200	20.0	20.0	75	150
EMEB225220	22.0	25.0	80	150
EMEB225250	25.0	25.0	80	150



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 刃長為刃徑之5倍，適合側面大面積加工。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. The blade length is five times as the diameter, suitable for the processing of large lateral surface.
3. Optimized performance by the use of water-soluble cutting fluid.

EMEB

MG

TiAlN

35°

HRC 52°



端銑刀-長刃型四刃

Long Flute End Mills - 4 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
EMEB406030	3.0	6.0	15	75
EMEB406040	4.0	6.0	20	75
EMEB406050	5.0	6.0	25	75
EMEB406060	6.0	6.0	30	75
EMEB408080	8.0	8.0	35	100
EMEB410100	10.0	10.0	45	100
EMEB412120	12.0	12.0	50	100
EMEB416140	14.0	16.0	70	150
EMEB416160	16.0	16.0	70	150
EMEB420180	18.0	20.0	75	150
EMEB420200	20.0	20.0	75	150
EMEB425220	22.0	25.0	80	150
EMEB425250	25.0	25.0	80	150



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 全長加長，適用於深部位之加工刀具。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. Full-length extension, applicable to the processing of deep parts.
3. Optimized performance by the use of water-soluble cutting fluid.

EMED

MG

TiAlN

35°

HRC 52°



端銑刀-長柄型二刃

Long Shank End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
EMED206030	3.0	6.0	8	75
EMED204040	4.0	4.0	10	75
EMED206040	4.0	6.0	10	75
EMED206050	5.0	6.0	13	75
EMED206060	6.0	6.0	15	75
EMED206060	6.0	6.0	15	100
EMED208080	8.0	8.0	20	100
EMED210100	10.0	10.0	25	100
EMED212120	12.0	12.0	30	100
EMED216140	14.0	16.0	35	150
EMED216160	16.0	16.0	40	150
EMED220180	18.0	20.0	40	150
EMED220200	20.0	20.0	40	150
EMED225220	22.0	25.0	40	150
EMED225250	25.0	25.0	40	150



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 全長加長，適用於深部位之加工刀具。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. Full-length extension, applicable to the processing of deep parts.
3. Optimized performance by the use of water-soluble cutting fluid.

EMED

MG

TiAlN

35°

HRC 52°



端銑刀-長柄型四刃

Long Shank End Mills - 4 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
EMED406030	3.0	6.0	8	75
EMED404040	4.0	4.0	10	75
EMED406040	4.0	6.0	10	75
EMED406050	5.0	6.0	13	75
EMED406060	6.0	6.0	15	75
EMED406060	6.0	6.0	15	100
EMED408080	8.0	8.0	20	100
EMED410100	10.0	10.0	25	100
EMED412120	12.0	12.0	30	100
EMED416140	14.0	16.0	35	150
EMED416160	16.0	16.0	40	150
EMED420180	18.0	20.0	40	150
EMED420200	20.0	20.0	40	150
EMED425220	22.0	25.0	40	150
EMED425250	25.0	25.0	40	150



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 從低轉速到高轉速進行3D精密加工。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. 3-D precise processing with the rotation speed from low to high.
3. Optimized performance by the use of water-soluble cutting fluid.

BNEA

MG

TIALN

35°

HRC 52°



## 球銑刀-標準型二刃 Ball Nose Standard End Mills - 2 Flute

產品編號 Code No	球頭半徑 Radius	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
BNEA204010	0.5R	1.0	4.0	2	50
BNEA204015	0.75R	1.5	4.0	3	50
BNEA204020	1.0R	2.0	4.0	4	50
BNEA204025	1.25R	2.5	4.0	5	50
BNEA203030	1.5R	3.0	3.0	6	50
BNEA204030	1.5R	3.0	4.0	6	50
BNEA204040	2.0R	4.0	4.0	8	50
BNEA206010	0.5R	1.0	6.0	2	50
BNEA206015	0.75R	1.5	6.0	3	50
BNEA206020	1.0R	2.0	6.0	4	50
BNEA206025	1.25R	2.5	6.0	5	50
BNEA206030	1.5R	3.0	6.0	6	50
BNEA206040	2.0R	4.0	6.0	8	50
BNEA206050	2.5R	5.0	6.0	10	50
BNEA206060	3.0R	6.0	6.0	12	50
BNEA208070	3.5R	7.0	8.0	14	60
BNEA208080	4.0R	8.0	8.0	16	60
BNEA210100	5.0R	10.0	10.0	20	75
BNEA212120	6.0R	12.0	12.0	24	75
BNEA216160	8.0R	16.0	16.0	32	100



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 從低轉速到高轉速進行3D精密加工。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. 3-D precise processing with the rotation speed from low to high.
3. Optimized performance by the use of water-soluble cutting fluid.

BNEA

MG

TIALN

35°

HRC 52°



## 球銑刀-標準型四刃 Ball Nose Standard End Mills - 4 Flute

產品編號 Code No	球頭半徑 Radius	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
BNEA403030	1.5R	3.0	3.0	6	50
BNEA404030	1.5R	3.0	4.0	6	50
BNEA404040	2.0R	4.0	4.0	8	50
BNEA406030	1.5R	3.0	6.0	6	50
BNEA406040	2.0R	4.0	6.0	8	50
BNEA406050	2.5R	5.0	6.0	10	50
BNEA406060	3.0R	6.0	6.0	12	50
BNEA408070	3.5R	7.0	8.0	14	60
BNEA408080	4.0R	8.0	8.0	16	60
BNEA410100	5.0R	10.0	10.0	20	75
BNEA412120	6.0R	12.0	12.0	24	75
BNEA416160	8.0R	16.0	16.0	32	100



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 從低轉速到高轉速進行3D精密加工。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. 3-D precise processing with the rotation speed from low to high.
3. Optimized performance by the use of water-soluble cutting fluid.

BNEED

MG

TiAlN

35

HRC 52



OIL



## 球銑刀-長柄型二刃 Ball Nose Long Shank End Mills - 2 Flute

產品編號 Code No	球頭半徑 Radius	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
BNED206010	0.5R	1.0	6.0	2	75
BNED206015	0.75R	1.5	6.0	3	75
BNED206020	1.0R	2.0	6.0	4	75
BNED206025	1.25R	2.5	6.0	5	75
BNED206030	1.5R	3.0	6.0	6	75
BNED204040	2.0R	4.0	4.0	8	75
BNED206040	2.0R	4.0	6.0	8	75
BNED206050	2.5R	5.0	6.0	10	75
BNED206060	3.0R	6.0	6.0	12	75
BNEE206060	3.0R	6.0	6.0	12	100
BNED208070	3.5R	7.0	8.0	14	100
BNED208080	4.0R	8.0	8.0	16	100
BNEE208080	4.0R	8.0	8.0	16	150
BNED210100	5.0R	10.0	10.0	20	100
BNEE210100	5.0R	10.0	10.0	20	150
BNED212120	6.0R	12.0	12.0	24	100
BNEE212120	6.0R	12.0	12.0	24	150
BNED216160	8.0R	16.0	16.0	32	150
BNED220200	10.0R	20.0	20.0	40	150
BNED225250	12.5R	25.0	25.0	40	150



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 從低轉速到高轉速進行3D精密加工。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. 3-D precise processing with the rotation speed from low to high.
3. Optimized performance by the use of water-soluble cutting fluid.

BNEED

MG

TiAlN

35

HRC 52



OIL



## 球銑刀-長柄型四刃 Ball Nose Long Shank End Mills - 4 Flute

產品編號 Code No	球頭半徑 Radius	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
BNED406030	1.5R	3.0	6.0	6	75
BNED404040	2.0R	4.0	4.0	8	75
BNED406040	2.0R	4.0	6.0	8	75
BNED406050	2.5R	5.0	6.0	10	75
BNED406060	3.0R	6.0	6.0	12	75
BNEE406060	3.0R	6.0	6.0	12	100
BNED408070	3.5R	7.0	8.0	14	100
BNED408080	4.0R	8.0	8.0	16	100
BNEE408080	4.0R	8.0	8.0	16	150
BNED410100	5.0R	10.0	10.0	20	100
BNEE410100	5.0R	10.0	10.0	20	150
BNED412120	6.0R	12.0	12.0	24	100
BNEE412120	6.0R	12.0	12.0	24	150
BNED416160	8.0R	16.0	16.0	32	150
BNED420200	10.0R	20.0	20.0	40	150
BNED425250	12.5R	25.0	25.0	40	150



## HHEA

MG

TiAlN

45°

HRC 52°



OIL



## 高螺旋端銑刀-標準型二刃 High Helix Standard End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
HHEA206010	1.0	6.0	2.5	50
HHEA206020	2.0	6.0	5	50
HHEA206030	3.0	6.0	8	50
HHEA206040	4.0	6.0	10	50
HHEA206050	5.0	6.0	13	50
HHEA206060	6.0	6.0	15	50
HHEA208080	8.0	8.0	20	60
HHEA210100	10.0	10.0	25	75
HHEA212120	12.0	12.0	30	75
HHEA216140	14.0	16.0	35	100
HHEA216160	16.0	16.0	40	100
HHEA220180	18.0	20.0	40	100
HHEA220200	20.0	20.0	40	100
HHEA225220	22.0	25.0	40	100
HHEA225250	25.0	25.0	40	100

## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel
2. Optimized performance by the use of water-soluble cutting fluid.



## HHEA

MG

TiAlN

45°

HRC 52°



OIL



## 高螺旋端銑刀-標準型三刃 High Helix Standard End Mills - 3 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
HHEA306030	3.0	6.0	8	50
HHEA306040	4.0	6.0	10	50
HHEA306050	5.0	6.0	13	50
HHEA306060	6.0	6.0	15	50
HHEA308080	8.0	8.0	20	60
HHEA310100	10.0	10.0	25	75
HHEA312120	12.0	12.0	30	75
HHEA316140	14.0	16.0	35	100
HHEA316160	16.0	16.0	40	100
HHEA320180	18.0	20.0	40	100
HHEA320200	20.0	20.0	40	100
HHEA325220	22.0	25.0	40	100
HHEA325250	25.0	25.0	40	100

## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel
2. Optimized performance by the use of water-soluble cutting fluid.



特點:

1. 加工不銹鋼材質，效果最佳。
2. 使用水溶性切削液，效果最佳化。

Features

1. Best performance in processing stainless steel.
2. Optimized performance by the use of water-soluble cutting fluid.

# HHEB



## 高螺旋端銑刀-長刃型二刃 High Helix Long Flute End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
HHEB206030	3.0	6.0	15	75
HHEB206040	4.0	6.0	20	75
HHEB206050	5.0	6.0	25	75
HHEB206060	6.0	6.0	30	75
HHEB208080	8.0	8.0	35	100
HHEB210100	10.0	10.0	45	100
HHEB212120	12.0	12.0	50	100
HHEB214160	14.0	16.0	70	150
HHEB216160	16.0	16.0	70	150
HHEB218200	18.0	20.0	75	150
HHEB220200	20.0	20.0	75	150
HHEB222250	22.0	25.0	80	150
HHEB225250	25.0	25.0	80	150



特點:

1. 加工不銹鋼材質，效果最佳。
2. 使用水溶性切削液，效果最佳化。

Features

1. Best performance in processing stainless steel.
2. Optimized performance by the use of water-soluble cutting fluid.

# HHEB



## 高螺旋端銑刀-長刃型三刃 High Helix Long Flute End Mills - 3 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	刃長 L.O.C	全長 O.A.L
HHEB306030	3.0	6.0	15	75
HHEB306040	4.0	6.0	20	75
HHEB306050	5.0	6.0	25	75
HHEB306060	6.0	6.0	30	75
HHEB308080	8.0	8.0	35	100
HHEB310100	10.0	10.0	45	100
HHEB312120	12.0	12.0	50	100
HHEB314160	14.0	16.0	70	150
HHEB316160	16.0	16.0	70	150
HHEB318200	18.0	20.0	75	150
HHEB320200	20.0	20.0	75	150
HHEB322250	22.0	25.0	80	150
HHEB325250	25.0	25.0	80	150



CREA

MG

TiAlN

35°

HRC 52°



OIL



## 圓偶角銑刀-標準型二刃 Corner Radius Standard End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	R角 Comer	柄徑 Shank	刃長 L.O.C	全長 O.A.L
CREA 204010-02	1.0	0.2R	4.0	2.5	50
CREA 204015-02	1.5	0.2R	4.0	4	50
CREA 204015-03	1.5	0.3R	4.0	4	50
CREA 204020-02	2.0	0.2R	4.0	5	50
CREA 204020-03	2.0	0.3R	4.0	5	50
CREA 204030-02	3.0	0.2R	4.0	8	50
CREA 204030-03	3.0	0.3R	4.0	8	50
CREA 204030-05	3.0	0.5R	4.0	8	50
CREA 204040-02	4.0	0.2R	4.0	10	50
CREA 204040-03	4.0	0.3R	4.0	10	50
CREA 204040-05	4.0	0.5R	4.0	10	50
CREA 206060-02	6.0	0.2R	6.0	15	50
CREA 206060-03	6.0	0.3R	6.0	15	50
CREA 206060-05	6.0	0.5R	6.0	15	50
CREA 206060-10	6.0	1.0R	6.0	15	50
CREA 206060-15	6.0	1.5R	6.0	15	50
CREA 208080-02	8.0	0.2R	8.0	20	60
CREA 208080-03	8.0	0.3R	8.0	20	60
CREA 208080-05	8.0	0.5R	8.0	20	60
CREA 208080-10	8.0	1.0R	8.0	20	60
CREA 208080-15	8.0	1.5R	8.0	20	60
CREA 210100-02	10.0	0.2R	10.0	25	75
CREA 210100-05	10.0	0.5R	10.0	25	75
CREA 210100-10	10.0	1.0R	10.0	25	75
CREA 210100-15	10.0	1.5R	10.0	25	75
CREA 210100-20	10.0	2.0R	10.0	25	75
CREA 212120-02	12.0	0.2R	12.0	30	75
CREA 212120-05	12.0	0.5R	12.0	30	75
CREA 212120-10	12.0	1.0R	12.0	30	75
CREA 212120-15	12.0	1.5R	12.0	30	75
CREA 212120-20	12.0	2.0R	12.0	30	75

## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 可同時加工平面及R角。
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. Applicable to the processing of planes and R angles.
3. Optimized performance by the use of water-soluble cutting fluid.



CREA

MG

TiAlN

35°

HRC 52°

5

OIL

R

R

## 圓偶角銑刀-標準型四刃 Corner Radius Standard End Mills - 4 Flute

產品編號 Code No	刃徑 Dia	R角 Comer	柄徑 Shank	刃長 L.O.C	全長 O.A.L
CREA 40 4030-02	3.0	0.2R	4.0	8	50
CREA 40 4030-03	3.0	0.3R	4.0	8	50
CREA 40 4030-05	3.0	0.5R	4.0	8	50
CREA 40 4040-02	4.0	0.2R	4.0	10	50
CREA 40 4040-03	4.0	0.3R	4.0	10	50
CREA 40 4040-05	4.0	0.5R	4.0	10	50
CREA 40 6060-02	6.0	0.2R	6.0	15	50
CREA 40 6060-03	6.0	0.3R	6.0	15	50
CREA 40 6060-05	6.0	0.5R	6.0	15	50
CREA 40 6060-10	6.0	1.0R	6.0	15	50
CREA 40 6060-15	6.0	1.5R	6.0	15	50
CREA 40 8080-02	8.0	0.2R	8.0	20	60
CREA 40 8080-03	8.0	0.3R	8.0	20	60
CREA 40 8080-05	8.0	0.5R	8.0	20	60
CREA 40 8080-10	8.0	1.0R	8.0	20	60
CREA 40 8080-15	8.0	1.5R	8.0	20	60
CREA 41 0100-02	10.0	0.2R	10.0	25	75
CREA 41 0100-05	10.0	0.5R	10.0	25	75
CREA 41 0100-10	10.0	1.0R	10.0	25	75
CREA 41 0100-15	10.0	1.5R	10.0	25	75
CREA 41 0100-20	10.0	2.0R	10.0	25	75
CREA 41 2120-02	12.0	0.2R	12.0	30	75
CREA 41 2120-05	12.0	0.5R	12.0	30	75
CREA 41 2120-10	12.0	1.0R	12.0	30	75
CREA 41 2120-15	12.0	1.5R	12.0	30	75
CREA 41 2120-20	12.0	2.0R	12.0	30	75

## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 可同時加工平面及R角
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. Applicable to the processing of planes and R angles.
3. Optimized performance by the use of water-soluble cutting fluid.



# CRED

MG

TiAlN

35°

HRC 52°



## 圓偶角銑刀-長柄二刃 Corner Radius Standard End Mills - 2 Flute

產品編號 Code No	刃徑 Dia	R角 Comer	柄徑 Shank	刃長 L.O.C	全長 O.A.L
CRED204010-02	1.0	0.2R	4.0	2.5	75
CRED204015-02	1.5	0.2R	4.0	4	75
CRED204015-03	1.5	0.3R	4.0	4	75
CRED204020-02	2.0	0.2R	4.0	5	75
CRED204020-03	2.0	0.3R	4.0	5	75
CRED204030-02	3.0	0.2R	4.0	8	75
CRED204030-03	3.0	0.3R	4.0	8	75
CRED204030-05	3.0	0.5R	4.0	8	75
CRED204040-02	4.0	0.2R	4.0	10	75
CRED204040-03	4.0	0.3R	4.0	10	75
CRED204040-05	4.0	0.5R	4.0	10	75
CRED206060-02	6.0	0.2R	6.0	15	75
CRED206060-03	6.0	0.3R	6.0	15	75
CRED206060-05	6.0	0.5R	6.0	15	75
CRED206060-10	6.0	1.0R	6.0	15	75
CRED206060-15	6.0	1.5R	6.0	15	75
CRED206060-02	6.0	0.2R	6.0	15	100
CRED206060-05	6.0	0.5R	6.0	15	100
CRED206060-10	6.0	1.0R	6.0	15	100
CRED206060-15	6.0	1.5R	6.0	15	100
CRED208080-02	8.0	0.2R	8.0	20	100
CRED208080-03	8.0	0.3R	8.0	20	100
CRED208080-05	8.0	0.5R	8.0	20	100
CRED208080-10	8.0	1.0R	8.0	20	100
CRED208080-15	8.0	1.5R	8.0	20	100
CRED210100-02	10.0	0.2R	10.0	25	100
CRED210100-05	10.0	0.5R	10.0	25	100
CRED210100-10	10.0	1.0R	10.0	25	100
CRED210100-15	10.0	1.5R	10.0	25	100
CRED210100-20	10.0	2.0R	10.0	25	100
CRED212120-02	12.0	0.2R	12.0	30	100
CRED212120-05	12.0	0.5R	12.0	30	100
CRED212120-10	12.0	1.0R	12.0	30	100
CRED212120-15	12.0	1.5R	12.0	30	100
CRED212120-20	12.0	2.0R	12.0	30	100

### 特點:

1. 加工不銹鋼材質，效果最佳。
2. 可同時加工平面及R角
3. 使用水溶性切削液，效果最佳化。

### Features

1. Best performance in processing stainless steel.
2. Applicable to the processing of planes and R angles.
3. Optimize performance by the use of water-soluble cutting fluid.



## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 可同時加工平面及R角
3. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. Applicable to the processing of planes and R angles.
3. Optimized performance by the use of water-soluble cutting fluid.

# CRED

MG

TiAlN

35°

HRC 52

OIL

## 圓偶角銑刀-長柄四刃 Corner Radius Long Shank End Mills - 4 Flute

產品編號 Code No	刃徑 Dia	R角 Corner	柄徑 Shank	刃長 L.O.C	全長 O.A.L
CRED404010-02	1	0.2R	4.0	2.5	75
CRED404015-02	1.5	0.2R	4.0	4	75
CRED404015-03	1.5	0.3R	4.0	4	75
CRED404020-02	2.0	0.2R	4.0	5	75
CRED404020-03	2.0	0.3R	4.0	5	75
CRED404030-02	3.0	0.2R	4.0	8	75
CRED404030-03	3.0	0.3R	4.0	8	75
CRED404030-05	3.0	0.5R	4.0	8	75
CRED404040-02	4.0	0.2R	4.0	10	75
CRED404040-03	4.0	0.3R	4.0	10	75
CRED404040-05	4.0	0.5R	4.0	10	75
CRED406060-02	6.0	0.2R	6.0	15	75
CRED406060-03	6.0	0.3R	6.0	15	75
CRED406060-05	6.0	0.5R	6.0	15	75
CRED406060-10	6.0	1.0R	6.0	15	75
CRED406060-15	6.0	1.5R	6.0	15	75
CRED406060-02	6.0	0.2R	6.0	15	100
CRED406060-05	6.0	0.5R	6.0	15	100
CRED406060-10	6.0	1.0R	6.0	15	100
CRED406060-15	6.0	1.5R	6.0	15	100
CRED408080-02	8.0	0.2R	8.0	20	100
CRED408080-03	8.0	0.3R	8.0	20	100
CRED408080-05	8.0	0.5R	8.0	20	100
CRED408080-10	8.0	1.0R	8.0	20	100
CRED408080-15	8.0	1.5R	8.0	20	100
CRED410100-02	10.0	0.2R	10.0	25	100
CRED410100-05	10.0	0.5R	10.0	25	100
CRED410100-10	10.0	1.0R	10.0	25	100
CRED410100-15	10.0	1.5R	10.0	25	100
CRED410100-20	10.0	2.0R	10.0	25	100
CRED412120-02	12.0	0.2R	12.0	30	100
CRED412120-03	12.0	0.5R	12.0	30	100
CRED412120-05	12.0	1.0R	12.0	30	100
CRED412120-15	12.0	1.5R	12.0	30	100
CRED412120-20	12.0	2.0R	12.0	30	100



SCDA

MG

TiAlN

HRC  
52°

鎢鋼鑽頭-短刃型

Corner Radius Long Shank End Mills - 4 Flute

產品編號 Code No	刃徑 Dia	柄徑 Shank	溝長 L.O.C	全長 O.A.L
SCDA2030030	3.0	3.0	16	46
SCDA2031031	3.1	3.1	18	49
SCDA2032032	3.2	3.2		
SCDA2033033	3.3	3.3		
SCDA2034034	3.4	3.4	20	52
SCDA2035035	3.5	3.5		
SCDA2036036	3.6	3.6		
SCDA2037037	3.7	3.7	22	55
SCDA2038038	3.8	3.8		
SCDA2039039	3.9	3.9		
SCDA2040040	4.0	4.0	24	58
SCDA2041041	4.1	4.1		
SCDA2042042	4.2	4.2		
SCDA2043043	4.3	4.3	26	62
SCDA2044044	4.4	4.4		
SCDA2045045	4.5	4.5		
SCDA2046046	4.6	4.6	28	66
SCDA2047047	4.7	4.7		
SCDA2048048	4.8	4.8		
SCDA2049049	4.9	4.9	31	70
SCDA2050050	5.0	5.0		
SCDA2051051	5.1	5.1		
SCDA2052052	5.2	5.2	31	70
SCDA2053053	5.3	5.3		
SCDA2054054	5.4	5.4		
SCDA2055055	5.5	5.5	31	70
SCDA2056056	5.6	5.6		
SCDA2057057	5.7	5.7		
SCDA2058058	5.8	5.8	31	70
SCDA2059059	5.9	5.9		
SCDA2060060	6.0	6.0		
SCDA2061061	6.1	6.1	31	70
SCDA2062062	6.2	6.2		
SCDA2063063	6.3	6.3		
SCDA2064064	6.4	6.4	31	70
SCDA2065065	6.5	6.5		
SCDA2066066	6.6	6.6		
SCDA2067067	6.7	6.7	31	70

特點:

1. 加工不銹鋼材質，效果最佳。
2. 使用水溶性切削液，效果最佳化。

Features

1. Best performance in processing stainless steel
2. Optimized performance by the use of water-soluble cutting fluid.



SCDA

MG

TiAlN

HRC  
5.2

鎢鋼鑽頭-短刃型

Micro Grain Carbide Drills - Short

產品編號 Code No	刃徑 Dia	柄徑 Shank	溝長 L.O.C	全長 O.A.L
SCDA2068068	6.8	6.8	34	74
SCDA2069069	6.9	6.9		
SCDA2070070	7	7		
SCDA2071071	7.1	7.1		
SCDA2072072	7.2	7.2		
SCDA2073073	7.3	7.3		
SCDA2074074	7.4	7.4	37	79
SCDA2075075	7.5	7.5		
SCDA2076076	7.6	7.6		
SCDA2077077	7.7	7.7		
SCDA2078078	7.8	7.8		
SCDA2079079	7.9	7.9		
SCDA2080080	8	8	40	84
SCDA2081081	8.1	8.1		
SCDA2082082	8.2	8.2		
SCDA2083083	8.3	8.3		
SCDA2084084	8.4	8.4		
SCDA2085085	8.5	8.5		
SCDA2086086	8.6	8.6	51	102
SCDA2087087	8.7	8.7		
SCDA2088088	8.8	8.8		
SCDA2089089	8.9	8.9		
SCDA2090090	9	9		
SCDA2091091	9.1	9.1		
SCDA2092092	9.2	9.2	43	89
SCDA2093093	9.3	9.3		
SCDA2094094	9.4	9.4		
SCDA2095095	9.5	9.5	47	95
SCDA2096096	9.6	9.6		
SCDA2097097	9.7	9.7		
SCDA2098098	9.8	9.8	51	102
SCDA2099099	9.9	9.9		
SCDA2100100	10	10		
SDCA2105105	10.5	10.5	47	95
SCDA2110110	11	11		
SCDA2115115	11.5	11.5		
SCDA2120120	12	12	51	102
SCDA2125125	12.5	12.5		
SCDA2130130	13	13		

## 特點:

1. 加工不銹鋼材質，效果最佳。
2. 使用水溶性切削液，效果最佳化。

## Features

1. Best performance in processing stainless steel.
2. Optimized performance by the use of water-soluble cutting fluid.